

## 2SEE FAQs

### Mount

Q. Can I mount the camera to my display?

A. Yes. Using the mount attached to the 2SEE camera, you can easily mount it on any display with a maximum depth of 1½".

Q. How does the attached mount work?

A. The mount unfolds from the bottom of the camera. You don't have to use any force. There are soft-grip pads already on the arms that help protect your display and keep the camera stable.

1. With the camera facing forward, unfold the arms of the mount so that the small arm is pointing in the same direction as the camera, and the long arm is pointing down.
2. The short arm will rest on the top of your display. The long arm will rest behind your display.
3. While on the display, adjust the angles of the camera and arms slightly until it is in a stable position.

### Environment

Q. Will the microphones on the 2SEE work in a noisy space?

A. Yes. The 2SEE has a four-microphone array that's perfect for spaces where you're going to have background noise. It has an Active Noise Reduction feature to help make your voice dominant and background noise less of an issue.

Q. Will the 2SEE work in a large room?

A. Yes. The 2SEE has exceptional sound quality up to 8 meters away.

### Setup/Installation

Q. Which video conferencing platforms will work with my 2SEE camera?

A. Any platform that is compatible with a USB camera or a built-in laptop camera will also work with the 2SEE.

Q. Do I need to install any drivers?

A. No. The 2SEE is a plug-and-play camera. The drivers will install automatically when you plug it in to your computer.