## TeamCam 1080p HD PTZ USB Camera

Affordable, belt-driven, 90° FOV, and low-light performance in a compact form factor

The TeamCam HD PTZ USB camera is ideal for applications that require a **budget-friendly enterprise grade camera** that is unobtrusive when installed. With a USB 2.0 interface for installation, it's ideal for deployment in huddle spaces, small classrooms and meeting rooms as well as mobile cart designs.

Amazing image quality is made possible with a **3x digital zoom along with a Sony 1/3.8 CMOS dynamic sensor** that provides 1280x720 and 1920x1080 resolutions. A belt-driven PTZ mechanism ensures whisper-quiet operation while offering **340° of pan, 200° of tilt** and a wide 90° FOV to eliminate distortion.

At just 5" tall and under 2.5lbs, it's ideal for desktops as well as wall/tripod mounts and is easily controlled with an included IR remote control. **With up to seven camera position presets,** you can quickly focus on any location within the room with a single button press. A high-quality shielded USB cable is included to assist with quick installation.

## Website: https://vdo360.com/camera/teamcam/

## **Key Information:**

| Part Number: VPTZH-05             | MSRP: \$299                                                                                                        |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Dual IR Receivers (Base and Lens) | Min focal distance: 3.9"                                                                                           |
| Adjustable bottom mount plate     | Focal length: 3.5mm                                                                                                |
| Power: 12V DC input at 2A         | Tilt speed: 85° per second                                                                                         |
| Sensor: CMOS 1/3.8                | Minimum illumination: 0.9 lux                                                                                      |
| Autofocus                         | SNR: >40db                                                                                                         |
| Frame rate: 25fps                 | FOV: 90 <sup>o</sup>                                                                                               |
|                                   | Dual IR Receivers (Base and Lens)Adjustable bottom mount platePower: 12V DC input at 2ASensor: CMOS 1/3.8Autofocus |

I for deployment in huddle spaces, small ting rooms as well as mobile cart designs. ity is made possible with a **3x digital zoom** /3.8 CMOS dynamic sensor that provides



